

Oilfield Tubular Goods Drilling & Production Equipment Commodities

2019 KENWORTH ALL AMERICAN 600HP DOUBLE PUMPERS TWIN PUMPER SPECIFICATION

TRIPLEX PUMPS

- Two 600 hp. OFM Short triplex pumps. High pressure pump rate of37 gpm at 10,394 psi, 75 gpm at 9,713 psi, 225 gpm at 3,886 psi, and 337 gpm at 2,591.4" plun gers.
- One 600 HP pump powered by truck engine and one 600 hp pump powered by a deck engine through an Allison transmission.
- One 784 Spicer transfer case driven by truck main propeller shaft to drive one triplex.
- One deck mounted Caterpillar 3406£/C 15 625 hp. . diesel engine . Tier 3 with radiator and batteries to drive opposite side triplex.
- 6061 Allison automatic transmission with electronic shift control.
- Dual 1810 drivelines for drive input to triplex pumps one from deck engine and one from 784 Remote controls and gauges mounted on platform next to truck transmission shift pad.

Mail: 40 Cypress Creek Parkway, #149; Houston, TX 77090 Yard/Shop/Office 2212 Dwyer Rd, Houston TX 77090 Office: 1.888.419.1115 Cell: 1.832.433.8467 Fax: 1.281.436.6015

Oilfield Tubular Goods
Drilling & Production
Equipment
Commodities

CHARGE PUMP SYSTEM

- 2 Gardner Denver 20th century 4 x 5 centrifugal pumps.
- Dual hose hook ups at each suction pott for the charge pumps.
- Charge pumps to be driven by the hyd. System.
- Discharge to the suction piping of the triplex pumps.

HYDRAULIC SYSTEM

- Hydraulic system to power charge pumps.
- Dual hydrostat hydraulic system to be powered off the main truck transmission.
- 50 gal oil reservoir with 30 GPM. Hyd. . cooler
- Dual thumb dial rheostat speed controls.

FLUID TANKS

- 2ea 10661 (420 gal min) holding tanks to be DOT specification 412 Internally coated with Corchem 243 I ea 4" inlet and I ea. 4" outlet with sst/viton butterfly valves.
- 3 " Girard vac.

Oilfield Tubular Goods Drilling & Production Equipment Commodities

TRUCKS

2018 T880 KENWORTH 605HP FOR TWIN PUMPER

ENGINE AND TRANSMISSION

- 605 horsepower Cummins ISX engine 2050 ft/lbs torque Heavy Duty Radiator And Fan Assembly Engine Oil Cooler And High Capacity Water Filter.
- Power Steering Single.
- Single Cab Filter Element Breather Sst.
- Rtlo 18913 Fuller Roadranger Transmission W Mounts.
- Heavy Duty 15.5 Ceramic Clutch Assembly.

FRAME AND EQUIPMENT

- 10 ¾" Main Frame With Full Steel Inse11 Full Length
- 3/8 " Outer And 5/16" Inner
- Steel Crossmembers
- Midship Bearings
- 3 Air Tanks For Additional Capacity
- 10 ' After frame For Platform
- 250"CA

Oilfield Tubular Goods Drilling & Production Equipment Commodities

TIRES AND WHEELS

- 385 Flotation Tires Front Bridgestone Mounted On Alcoa Aluminum Wheels 11 r 24.5 Bridgestone Tires Rear 12 Mounted On Accuride Steel Wheels.
- Heavy duty shock absorbers front and rear.

SUSPENSION SYSTEM FRONT AND REAR

- 20 K Front axle with heavy duty taper leaf springs 18-20 split progression.
- Front disc brakes with air chamber
- 46 k Rear Susp ens ion hendickson primax air ride
- Rear heav y 16.5' drums with air brake chambers
- Automatic slack adjusters front and rear
- 20k additi onal air ride steerable pusher axle mounted forward of the tandem suspension selectable pos.

CAB AND EQUIPMENT

- Heavy duty severe service cab suspension package
- Full gauge and instrumentation
- Trim level 3 with grey interior



Oilfield Tubular Goods Drilling & Production Equipment Commodities

- Air ride drivers seat high back
- Stationaty passenger seat
- Am/fm/xm/cd player sound system
- Day cab style glass passenger lower door glass and mirror
- Std mirrors
- Single exhaust
- 100 gal fuel drivers side, 80 gal pass side
- Tier 3 no aftertreatment system
- Cab paint white